

Motori NEMA monofase autofrenanti
NEMA single phase induction self-brake motors
Moteurs NEMA asynchrones monophasés autofreinants
Wechselstrombremsmotoren NEMA

Potenza / Power		rpm		Poli Poles	IEC frame	NEMA C FACE Mounting	In [A] 230V//60Hz	Rend.		Cn [Nm]		Cn [lb·in]		J- [kgm²]	J- [lb.ft²]	Coppia Frenante Brake Torque		WGT		C Dimension	
hp	kW																				
230V-115V 50-60Hz hp	230V-115V 50-60Hz kW	50Hz	60Hz									50Hz	60Hz			50Hz	60Hz	50Hz	60Hz		
1/4	0,18	2790	3348	2	IEC80	56C	1,56	54	56	0,62	0,51	5,46	4,55	0,00097	0,02302	5	44	12,4	27,34	313,0	12,32
1/4	0,18	1410	1692	4	IEC80	56C	1,48	57	59	1,22	1,02	10,80	9,00	0,00140	0,03322	5	44	11,7	25,8	313,0	12,32
1/4	0,18	910	1092	6	IEC80	56C	1,56	54	56	1,89	1,57	16,74	13,95	0,00250	0,05933	5	44	10,9	24,04	313,0	12,32
1/3	0,25	2780	3336	2	IEC80	56C	2,17	54	56	0,86	0,72	7,61	6,34	0,00097	0,02302	5	44	12,4	27,34	313,0	12,32
1/3	0,25	1400	1680	4	IEC80	56C	2,02	58	60	1,71	1,42	15,11	12,59	0,00140	0,03322	5	44	11,7	25,80	313,0	12,32
1/3	0,25	900	1080	6	IEC80	56C	2,09	56	58	2,65	2,21	23,51	19,59	0,00250	0,05933	5	44	10,9	24,04	313,0	12,32
1/2	0,37	2790	3348	2	IEC80	56C	2,99	58	60	1,27	1,06	11,22	9,35	0,00097	0,02302	5	44	12,4	27,34	313,0	12,32
1/2	0,37	1390	1668	4	IEC80	56C	2,94	59	61	2,54	2,12	22,53	18,77	0,00140	0,03322	5	44	11,7	25,80	313,0	12,32
1/2	0,37	900	1080	6	IEC80	56C	2,75	63	65	3,93	3,27	34,79	28,99	0,00250	0,05933	5	44	10,9	24,04	313,0	12,32
3/4	0,55	2780	3336	2	IEC80	56C	4,30	60	62	1,89	1,58	16,74	13,95	0,00097	0,02302	5	44	12,4	27,34	313,0	12,32
3/4	0,55	2780	3336	2	IEC80	143C	4,30	60	62	1,89	1,58	16,74	13,95	0,00097	0,02302	5	44	12,4	27,34	314,5	12,38
3/4	0,55	2780	3336	2	IEC80	145C	4,30	60	62	1,89	1,58	16,74	13,95	0,00097	0,02302	5	44	12,4	27,34	314,5	12,38
3/4	0,55	1400	1680	4	IEC80	56C	4,30	60	62	3,75	3,13	33,25	27,70	0,00140	0,03322	5	44	11,7	25,80	313,0	12,32
3/4	0,55	1400	1680	4	IEC80	143C	4,30	60	62	3,75	3,13	33,25	27,70	0,00140	0,03322	5	44	11,7	25,80	314,5	12,38
3/4	0,55	1400	1680	4	IEC80	145C	4,30	60	62	3,75	3,13	33,25	27,70	0,00140	0,03322	5	44	11,7	25,80	314,5	12,38
1	0,75	2770	3324	2	IEC80	56C	5,67	62	64	2,59	2,16	22,91	19,09	0,00097	0,02302	5	44	12,4	27,34	313,0	12,32
1	0,75	2770	3324	2	IEC80	143C	5,67	62	64	2,59	2,16	22,91	19,09	0,00097	0,02302	5	44	12,4	27,34	314,5	12,38
1	0,75	2770	3324	2	IEC80	145C	5,67	62	64	2,59	2,16	22,91	19,09	0,00097	0,02302	5	44	12,4	27,34	314,5	12,38
1	0,75	1380	1656	4	IEC80	56C	5,67	62	64	5,19	4,33	45,99	38,33	0,00170	0,04034	10	89	12,3	27,12	317,0	12,48
1	0,75	1380	1656	4	IEC80	143C	5,67	62	64	5,19	4,33	45,99	38,33	0,00170	0,04034	10	89	12,3	27,12	318,5	12,54
1	0,75	1380	1656	4	IEC80	145C	5,67	62	64	5,19	4,33	45,99	38,33	0,00170	0,04034	10	89	12,3	27,12	318,5	12,54
1 1/2	1,10	2790	3348	2	IEC80	56C	8,06	64	66	3,77	3,14	33,36	27,80	0,00120	0,02848	5	44	13,0	28,67	313,0	12,32
1 1/2	1,10	2790	3348	2	IEC80	143C	8,06	64	66	3,77	3,14	33,36	27,80	0,00120	0,02848	5	44	13,0	28,67	314,5	12,38
1 1/2	1,10	2790	3348	2	IEC80	145C	8,06	64	66	3,77	3,14	33,36	27,80	0,00120	0,02848	5	44	13,0	28,67	314,5	12,38
1 1/2	1,10	2920	3504	2	IEC100	182C	8,06	64	66	3,60	3,00	31,88	26,57	0,00530	0,12577	16	142	27,2	59,98	427,0	16,81
1 1/2	1,10	2920	3504	2	IEC100	184C	8,06	64	66	3,60	3,00	31,88	26,57	0,00530	0,12577	16	142	27,2	59,98	427,0	16,81
1 1/2	1,10	1430	1716	4	IEC100	182C	8,06	64	66	7,35	6,12	65,10	54,25	0,00850	0,20171	16	142	28,0	61,74	427,0	16,81
1 1/2	1,10	1430	1716	4	IEC100	184C	8,06	64	66	7,35	6,12	65,10	54,25	0,00850	0,20171	16	142	28,0	61,74	427,0	16,81



Potenza / Power		rpm					In [A]	Rend.		Cn [Nm]		Cn [lb·in]		J- [kgm²]	J- [lb.ft²]	Coppia Frenante Brake Torque		WGT		C Dimension	
hp	kW																				
230V-115V 50-60Hz hp	230V-115V 50-60Hz kW	50Hz	60Hz	Poli Poles	IEC frame	NEMA C FACE Mounting	230V//60Hz	50Hz	60Hz	50Hz	60Hz	50Hz	60Hz			[Nm]	[lb·in]	[Kg]	[lb]	Auto- frenante [mm]	Selfbrake [in]
1 1/2	1,10	930	1116	6	IEC100	182C	6,79	76	78	11,30	9,42	100,09	83,41	0,00900	0,21357	16	142	27,0	59,54	427,0	16,81
1 1/2	1,10	930	1116	6	IEC100	184C	6,79	76	78	11,30	9,42	100,09	83,41	0,00900	0,21357	16	142	27,0	59,54	427,0	16,81
2	1,50	2750	3300	2	IEC80	56C	10,66	66	68	5,21	4,34	46,16	38,47	0,00130	0,03085	10	89	14,3	31,53	317,0	12,48
2	1,50	2750	3300	2	IEC80	143C	10,66	66	68	5,21	4,34	46,16	38,47	0,00130	0,03085	10	89	14,3	31,53	318,5	12,54
2	1,50	2750	3300	2	IEC80	145C	10,66	66	68	5,21	4,34	46,16	38,47	0,00130	0,03085	10	89	14,3	31,53	318,5	12,54
2	1,50	2920	3504	2	IEC100	182C	10,66	66	68	4,91	4,09	43,47	36,23	0,00530	0,12577	16	142	27,2	59,98	427,0	16,81
2	1,50	2920	3504	2	IEC100	184C	10,66	66	68	4,91	4,09	43,47	36,23	0,00530	0,12577	16	142	27,2	59,98	427,0	16,81
2	1,50	1410	1692	4	IEC100	182C	10,99	64	66	10,16	8,47	90,03	75,02	0,00850	0,20171	16	142	28,0	61,74	427,0	16,81
2	1,50	1410	1692	4	IEC100	184C	10,99	64	66	10,16	8,47	90,03	75,02	0,00850	0,20171	16	142	28,0	61,74	427,0	16,81
2	1,50	920	1104	6	IEC100	182C	9,02	78	80	15,58	12,98	137,98	114,98	0,00950	0,22544	16	142	29,0	63,95	427,0	16,81
2	1,50	920	1104	6	IEC100	184C	9,02	78	80	15,58	12,98	137,98	114,98	0,00950	0,22544	16	142	29,0	63,95	427,0	16,81
3	2,20	2900	3480	2	IEC100	182C	14,33	72	74	7,25	6,04	64,20	53,50	0,00530	0,12577	16	142	27,2	59,98	427,0	16,81
3	2,20	2900	3480	2	IEC100	184C	14,33	72	74	7,25	6,04	64,20	53,50	0,00530	0,12577	16	142	27,2	59,98	427,0	16,81
3	2,20	2900	3480	2	IEC100	213C	14,33	72	74	7,25	6,04	64,20	53,50	0,00530	0,12577	16	142	27,2	59,98	429,0	16,89
3	2,20	2900	3480	2	IEC100	215C	14,33	72	74	7,25	6,04	64,20	53,50	0,00530	0,12577	16	142	27,2	59,98	429,0	16,89
3	2,20	1400	1680	4	IEC100	182C	14,74	70	72	15,01	12,51	132,98	110,82	0,00850	0,20171	16	142	28,0	61,74	427,0	16,81
3	2,20	1400	1680	4	IEC100	184C	14,74	70	72	15,01	12,51	132,98	110,82	0,00850	0,20171	16	142	28,0	61,74	427,0	16,81
3	2,20	1400	1680	4	IEC100	213C	14,74	70	72	15,01	12,51	132,98	110,82	0,00850	0,20171	16	142	28,0	61,74	429,0	16,89
3	2,20	1400	1680	4	IEC100	215C	14,74	70	72	15,01	12,51	132,98	110,82	0,00850	0,20171	16	142	28,0	61,74	429,0	16,89
4	3,00	2870	3444	2	IEC100	182C	18,27	77	79	9,99	8,32	88,46	73,71	0,00530	0,12577	16	142	29,0	63,95	427,0	16,81
4	3,00	2870	3444	2	IEC100	184C	18,27	77	79	9,99	8,32	88,46	73,71	0,00530	0,12577	16	142	29,0	63,95	427,0	16,81
4	3,00	2870	3444	2	IEC100	213C	18,27	77	79	9,99	8,32	88,46	73,71	0,00530	0,12577	16	142	29,0	63,95	429,0	16,89
4	3,00	2870	3444	2	IEC100	215C	18,27	77	79	9,99	8,32	88,46	73,71	0,00530	0,12577	16	142	29,0	63,95	429,0	16,89
5	3,75	2870	3444	2	IEC100	182C	23,14	76	78	12,48	10,40	110,57	92,14	0,00530	0,12577	16	142	29,0	63,95	427,0	16,81
5	3,75	2870	3444	2	IEC100	184C	23,14	76	78	12,48	10,40	110,57	92,14	0,00530	0,12577	16	142	29,0	63,95	427,0	16,81
5	3,75	2870	3444	2	IEC100	213C	23,14	76	78	12,48	10,40	110,57	92,14	0,00530	0,12577	16	142	29,0	63,95	429,0	16,89
5	3,75	2870	3444	2	IEC100	215C	23,14	76	78	12,48	10,40	110,57	92,14	0,00530	0,12577	16	142	29,0	63,95	429,0	16,89