

TIPO TYPE	DC				AC				DC - S				POS.DC			
	CF	Cicli/h Cycles/h	PB	Peso Weight	CF	Cicli/h Cycles/h	PB	Peso Weight	CF	Cicli/h Cycles/h	PB	Peso Weight	CF	Cicli/h Cycles/h	PB	Peso Weight
	Nm	⊝O	Watt	Kg	Nm	⊝O	VA	Kg	Nm	⊝O	Watt	Kg	Nm	⊝O	Watt	Kg
Ai50A	1	12500	12	3,9	-	-	-	-	-	-	-	-	-	-	-	-
Ai56B	1	12500	12	5,0	-	-	-	-	-	-	-	-	-	-	-	-
Ai56C	1	12500	12	5,0	-	-	-	-	-	-	-	-	-	-	-	-
Ai63A	4	10500	20	5,0	5	10500	40	5,0	3	10500	17	5,0	7,5	10500	11,5	4,05
Ai63B	4	10500	20	7,0	5	10500	40	7,0	3	10500	17	6,0	7,5	10500	11,5	4,65
Ai71A	5	18000	20	8,0	5	18000	40	8,0	4	18000	17	7,0	7,5	18000	11,5	6,15
Ai71B	5	16000	20	9,0	5	16000	40	9,0	4	16000	17	9,0	7,5	16000	11,5	7,75
Ai80A	8	9000	25	11,0	10	9000	70	11,0	9	9000	34	11,0	15,0	9000	16,0	9,10
Ai80B	8	9000	25	13,0	10	9000	70	13,0	9	9000	34	12,0	15,0	9000	16,0	10,40
Ai80C	8	9000	25	14,0	10	9000	70	14,0	9	9000	34	14,0	15,0	9000	16,0	11,60
Ai90S	16	13500	30	17,0	20	13500	120	17,0	10	13500	34	15,0	30,0	13500	16,0	12,60
Ai90L	16	11000	30	18,0	20	11000	120	18,0	10	11000	34	16,0	30,0	11000	16,0	14,10
Ai90LB	16	8000	30	20,0	20	8000	120	20,0	10	8000	34	18,0	30,0	8000	16,0	16,10
Ai100A	32	7200	40	25,5	40	7200	160	27,5	12	7200	40	22,5	60,0	7200	21,0	19,90
Ai100B	32	6000	40	30,0	40	6000	160	32,0	12	6000	40	27,0	60,0	6000	21,0	23,90
Ai112A	60	3600	50	38,0	70	3600	300	38,0	13	3600	40	33,0	120,0	3600	21,0	29,90
Ai132S	80	1100	55	56,0	100	1100	500	57,0	17	1100	40	48,0	240,0	1100	28,0	43,90
Ai132M	80	850	55	66,0	100	850	500	67,0	17	850	40	57,0	240,0	850	28,0	52,90
Ai132ML	80	800	55	68,0	100	800	500	69,0	17	800	40	59,0	240,0	800	28,0	54,90
Ai160M	150	750	85	87,0	150	750	600	85,0	23	750	45	75,0	480,0	750	38,0	70,00
Ai160L	150	750	85	97,0	150	750	600	95,0	23	750	45	83,0	480,0	750	38,0	80,00
Ai180M	260	200	100	129,0	300	200	600	140,0	-	-	-	-	480,0	200	-	131,00
Ai180L	260	200	100	154,0	300	200	600	155,0	-	-	-	-	480,0	200	-	146,00
Ai200L	400	100	100	174,0	300	100	600	175,0	-	-	-	-	480,0	100	-	166,00